

PENDING CLAIMS AS AMENDED

Please amend the claims as follows:

Please cancel claims 1-9 and 11, and substitute claims 12-21 for examination and allowance.

Claims 1 – 11 (Cancelled)

12. (New) A method for a CDMA communication system, comprising:
measuring downlink time offset experienced at a mobile station between downlink transmissions from base stations;
communicating said measured time offset from said mobile station to at least one of said base stations;
determining a downlink data frame time offset based on said measured time offset, wherein said downlink data frame time offset is in a multiple of predetermined number of chips;
communicating said downlink data frame time offset information to said mobile station.

13. (New) The method as recited in claim 12 wherein said communicating said downlink data frame time offset information is by way of communicating an Active Set Update message.

14. (New) The method as recited in claim 12 wherein said communicating said measured time offset is by way of communicating a measurement report message from said mobile station.

15. (New) The method as recited in claim 12 further comprising:
adjusting timing of a time offset adjuster in said mobile station for adjusting data symbol timing according to said downlink data frame time offset information and for identifying corresponding data symbols for a soft combining operation.

16. (New) The method as recited in claim 15 further comprising soft combining said corresponding data symbols.

17. (New) An apparatus for a CDMA communication system, comprising:
a transceiver coupled with a controller at a mobile station for:

measuring downlink time offset experienced at said mobile station between
downlink transmissions from base stations, and

communicating said measured time offset from said mobile station to at least one
of said base stations;

a transceiver coupled with a controller at said least one of said base stations for:

determining a downlink data frame time offset based on said measured time
offset, wherein said downlink data frame time offset is in a multiple of predetermined
number of chips, and

communicating said downlink data frame time offset information to said mobile
station.

18. (New) The apparatus as recited in claim 17 wherein said transceiver coupled with
said controller at said least one of said base stations further for communicating said downlink
data frame time offset information by way of communicating an Active Set Update message.

19. (New) The apparatus as recited in claim 17 wherein said transceiver coupled with
said controller at said mobile station further for communicating said measured time offset by way
of communicating a measurement report message from said mobile station.

20. (New) The apparatus as recited in claim 17 wherein said transceiver coupled with
said controller at said mobile station further for adjusting timing of a time offset adjuster in said
mobile station for adjusting data symbol timing according to said downlink data frame time
offset information and for identifying corresponding data symbols for a soft combining operation.

21. (New) The apparatus as recited in claim 20 wherein said transceiver coupled with said controller at said mobile station further for soft combining said corresponding data symbols.